

CBPS Supply (Page 64)

Four-Way Supply

Neck Size		Neck Velocity - V_N							
		300	400	500	600	700	800	1000	1200
6"	CFM	60	80	100	120	140	160	200	240
	Ps	<.010	.010	.020	.030	.040	.050	.080	.120
	Throw	1.5-2.0-2.5	1.5-2.5-3.0	2.0-3.0-4.0	2.5-3.5-4.5	3.0-4.5-5.5	3.5-5.0-6.0	4.0-6.0-7.0	5.0-7.5-9.0
	NC	<20	<20	<20	<20	21	24	32	38
8"	CFM	105	140	175	210	245	280	350	420
	Ps	<.010	.010	.020	.030	.040	.060	.090	.120
	Throw	1.5-2.5-3.0	2.0-3.0-4.0	2.5-4.0-5.0	3.5-5.0-6.0	4.0-5.5-7.0	4.5-6.5-8.0	5.5-8.0-10.0	6.5-9.5-11.5
	NC	<20	<20	<20	<20	25	31	37	42
10"	CFM	165	220	275	325	380	435	545	650
	Ps	0.01	.020	.030	.040	.060	.070	.110	.160
	Throw	3.0-4.0-5.0	3.5-5.5-6.5	4.5-6.5-8.0	5.5-8.0-10.0	6.0-9.0-11.0	7.0-10.5-12.5	9.0-13.0-15.5	10.5-15.5-18.5
	NC	<20	<20	<20	21	27	32	39	44
12"	CFM	235	315	395	470	550	630	790	940
	Ps	.010	.020	.030	.040	.060	.080	.120	.170
	Throw	2.5-3.5-4.0	3.0-4.5-5.5	3.5-5.5-6.5	4.5-7.0-8.5	5.5-8.0-9.5	6.0-7.0-11.0	7.5-11.5-14.0	9.0-13.5-16.0
	NC	<20	<20	20	26	32	37	42	>45
14"	CFM	325	430	535	640	750	860	1075	1275
	Ps	.010	.020	.030	.050	.060	.080	.130	.180
	Throw	2.0-3.0-3.5	2.5-4.0-5.0	3.5-5.0-6.0	4.0-6.0-7.0	4.5-7.0-8.5	5.5-8.0-10.0	6.5-10.0-12.0	7.5-11.5-14.0
	NC	<20	<20	<20	24	30	35	42	>45
16"	CFM	420	560	700	840	980	1120	1400	1680
	Ps	.020	.040	.060	.080	.110	.140	.220	.260
	Throw	3.0-4.0-5.0	4.0-6.0-7.0	5.0-8.0-11.0	6.0-9.0-12.0	8.0-11.0-14.0	9.0-13.0-16.0	10.0-15.0-19.0	12.0-17.0-22.0
	NC	<20	<20	26	34	39	43	>45	>45

NOTES:

1. Ps is static Pressure Loss in inches of H₂O
2. NC is based on 10db room attenuation (Re: 10⁻¹² watts)
3. Throw is iso-thermal air at 150, 100, 75 FPM terminal velocities.
4. The use of a balancing hood is recommended to balance the system.

CBPR Return (Page 64)

Neck Velocity - V_N		200	300	400	500	600	700	800
-Ps		.01	.02	.03	.05	.07	.10	.12
6" Diameter	CFM	40	60	80	100	120	140	160
8" Diameter	CFM	70	105	140	175	210	245	280
10" Diameter	CFM	110	165	220	275	330	385	440
12" Diameter	CFM	160	240	320	395	475	550	630
14" Diameter	CFM	215	320	430	535	640	750	855
16" Diameter	CFM	281	420	563	698	836	975	1114
18" Diameter	CFM	356	531	712	881	1056	1231	1406

SCBPS Diffuser (Page 64)

Neck Velocity - V_N		300	400	500	600	700	800	1000	1200
6"	CFM	60	80	100	120	135	155	195	235
	Ps	.012	.022	.034	.049	.066	.086	.135	.194
	An .200	1.00	1.50	1.50	2.00	2.50	3.00	3.50	4.00
	Ak .330	0.50	1.00	1.00	1.50	1.50	1.50	0.20	2.50
8"	CFM	105	140	175	210	245	280	350	420
	Ps	.012	.022	.034	.049	.066	.086	.135	.195
	An .350	2.25	3.00	3.50	4.50	5.25	6.00	7.50	9.00
	Ak .450	1.25	2.00	2.50	3.00	3.50	3.50	4.50	5.50
10"	CFM	165	220	275	325	380	435	545	655
	Ps	.012	.022	.034	.049	.066	.087	.135	.195
	An .550	3.50	4.50	5.50	7.00	8.00	9.00	11.50	13.50
	Ak .570	2.00	3.00	3.50	4.50	5.00	5.50	7.00	8.50
12"	CFM	235	315	395	470	550	630	785	945
	Ps	.014	.025	.039	.056	.076	.099	.155	.223
	An .790	5.00	6.00	7.50	9.50	11.00	12.50	15.50	18.50
	Ak .700	3.00	4.00	5.00	6.00	7.00	7.50	9.50	11.50
14"	CFM	320	430	535	640	750	855	1070	1285
	Ps	.016	.028	.044	.063	.086	.112	.175	.252
	An 1.070	6.00	7.50	9.50	11.50	13.50	15.50	19.00	23.00
	Ak .840	3.50	5.00	6.00	7.00	8.50	9.50	12.00	14.50

FPD12 (Page 61)

Neck Velocity		400	500	600	700	800	1000	1200	1400	1600
6"	CFM	80	100	120	135	155	195	235	275	315
	An .200	.008	.012	.019	.025	.033	.052	.074	.101	.131
	NC	<20	<20	<20	<20	<20	25	30	35	40
	Throw	4	5	5	6	7	8	9	10	11
7"	CFM	107	134	160	187	214	267	321	374	428
	An .275	.01	.015	.023	.031	.041	.064	.091	.125	.162
	NC	<20	<20	<20	<20	20	30	35	40	45
	Throw	4	5	6	7	8	10	11	12	13
8"	CFM	140	175	210	245	280	350	420	490	560
	An .350	.012	.019	.028	.038	.05	.078	.112	.153	.199
	NC	<20	<20	<20	<20	20	30	35	40	45
	Throw	5	6	7	8	9	11	12	14	15

Terminal Velocity of 75 FPM

An = Neck Area in Sq. Ft.

NC = Noise Criteria based on 10dB room absorption (Re: 10⁻¹² watts).