

UL181B-FX Listed Duct Tape

Stick to the Tape that Adheres to Industry Standards

Hart & Cooley continues its attention to detail by offering flexible duct tapes specially designed to meet your installation needs. With longer life and better adhesion, these tapes outperform cloth duct tapes, and they meet the stringent standards of Underwriter Laboratories.

Best of all, this UL-listed duct tape tears easily by hand.

Other features include:

- Comes in black or silver to match flex duct.
- 120 yards of tape—twice the length of standard cloth tape.
- Meets flexible duct installation requirements.
- Superior performance in extreme environments from -35°F to 260°F.
- Durable water-based adhesive works even in high humidity.
- Single-ply, 3 mil thickness for durability and strength.



UL181B-FX Listed Duct Tape



Features

- Easily tears by hand
- Acrylic water-based, all-weather adhesive
- UL-listed 181B-FX
- Single-ply polypropylene film
- Required by all major building codes
- Meets flexible duct installation requirements

Technical Data

	Imperial	Metric
Thickness:	3.0 mils (0.003")	0.0762 mm
Adhesion:		
Peel - to stainless steel	41 oz./inch width	11.4 N/2.5 cm
- to backing	31 oz./inch width	8.6 N/2.5 cm
Shear - Indefinite @	2.2 psi	15.2 KPa
Hot Shear - 150°F Indefinite @	2.2 psi	15.2 KPa
Tensile:	22 lb./inch	99.4 N/2.5 cm
Elongation:	150%	150%
Temperature Range:	-35°F to 260°F	-37°C to 127°C
Mold Growth:	0	0
Roll Size:	2" x 120 yards	

Important Information:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Users must determine the product suitability for the end use application and assume all risks and liabilities.

Offered by:



Hart & Cooley, Inc. 800.433.6341 *p*
 5030 Corporate Exchange Blvd. SE 616.656.8200 *p*
 Grand Rapids, MI 49512 800.223.8461 *f*
 info@hartcool.com 616.656.6399 *f*
 www.hartandcooley.com