



FEATURES

- Sturdy corrugated aluminum construction
- Includes male/female collars
- Shipped full length
- Packaged bulk in boxes in multiple quantities
- Non-combustible
- 10 year warranty

RECOMMENDED MAXIMUM OPERATING PRESSURES

- 12 in. W.C. positive for sizes up to 10 in.
- 8 in. W.C. positive for sizes 12 in. and larger
- 3 in. W.C. negative for all sizes
- Rated maximum air velocity: 5000 FPM.

SURFACE BURNING CHARACTERISTICS

- Flame spread: 0
- Smoke developed: 0

OPERATING TEMPERATURE RANGE

- -100°F to 400°F Continuous

SIZE AVAILABILITY

- Standard lengths: 6, 7-1/2 feet
- Diameters offered: 4"* , 5"- 10", 12", 14", 16", 18", 20", 22"* & 24"*

APPROVALS

- UL listed class 0 air duct to UL 181 (*These sizes are not UL listed)
- NFPA 90A & 90B
- HUD
- City of Los Angeles
- California Bureau of Home Furnishings
- Most Federal, State, and Local Codes and Standards.

JOB NAME: _____	SUBMITTED BY: _____	DATE: 3/12/08	SD-5024
LOCATION: _____		F040 Flexible Air Duct Class 0 Corrugated Aluminum	
ARCHITECT: _____			
ENGINEER: _____			
CONTRACTOR: _____			