



**FEATURES**

- Sturdy corrugated aluminum construction
- Includes male/female collars
- Shipped full length
- Packaged bulk in boxes in multiple quantities
- Non-combustible
- 10 year warranty

**RECOMMENDED MAXIMUM OPERATING PRESSURES**

- 3000 Pa. positive for sizes up to 254 mm
- 2000 Pa. positive for sizes 305 mm and larger
- 750 Pa. negative for all sizes
- Rated maximum air velocity: 25.4 m/s.

**SURFACE BURNING CHARACTERISTICS**

- Flame spread: 0
- Smoke developed: 0

**OPERATING TEMPERATURE RANGE**

- -38°C to 204°C Continuous

**SIZE AVAILABILITY**

- Standard length: 1.8 m, 2.3 m
- Diameters offered: 102\*, 127, 152, 178, 203, 229, 254, 305, 356, 406, 457, 508, 559\*, & 610\* mm

**APPROVALS**

- UL listed class 0 air duct to UL 181 (\*These sizes are not UL listed)
- NFPA 90A & 90B
- HUD
- City of Los Angeles
- California Bureau of Home Furnishings
- Most Federal, State, and Local Codes and Standards.

|                   |                     |  |          |
|-------------------|---------------------|--|----------|
| JOB NAME: _____   | SUBMITTED BY: _____ | DATE: 3/12/08  | SD-5024M |
| LOCATION: _____   |                     | <b>F040</b><br>Flexible Air Duct<br>Class 0<br>Corrugated Aluminum |          |
| ARCHITECT: _____  |                     |  |          |
| ENGINEER: _____   |                     |  |          |
| CONTRACTOR: _____ |                     |  |          |