

## 406 18" Baseboard Diffuser (Page 6)

Face Velocity		300	400	500	600	700	800
<b>Pressure Loss</b>		<b>.013</b>	<b>.022</b>	<b>.035</b>	<b>.048</b>	<b>.067</b>	<b>.088</b>
Ak .260	CFM	80	105	130	155	180	210
	Spread	4.5	6.5	7.5	8.5	9.5	11.0
	Throw	5.0	7.0	8.0	9.0	10.0	11.0

Terminal Velocity of 50 FPM

## 406 15" Baseboard Diffuser (Page 6)

Face Velocity		300	400	500	600	700	800	900	1000
15"	CFM	48	63	79	95	111	127	143	159
Ak .159	Ps	.005	.009	.014	.020	.027	.035	.044	.053
Throw	50	5.5	7.5	9.0	11.0	13.0	14.5	16.5	18.5
Spread	FPM	5.5	7.5	7.5	11.5	13.5	15.0	17.0	19.0
Throw	100	3.0	3.5	4.5	5.5	6.5	7.5	8.5	9.0
Spread	FPM	3.0	3.5	4.5	5.5	6.5	7.5	9.0	9.5
Throw	150	2.0	2.5	3.0	3.5	4.5	5.0	5.5	6.0
Spread	FPM	2.0	2.5	3.0	3.5	4.5	5.0	5.5	6.0

## 462 & 464 Baseboard Diffusers (Page 7, 8)

Airflow (CFM)		300	400	500	600	700	800
2 feet	CFM	55	75	95	110	130	150
27 sq. in. Ak .187	Spread	6.5	7.5	8.0	8.5	9.0	11.0
	Throw	7.0	8.0	9.5	10.5	12.0	13.0
	Pressure Loss	.009	.017	.029	.038	.054	.072
4 feet	CFM	110	150	185	225	260	300
54 sq. in. Ak .375	Spread	12.0	15.0	17.5	19.0	20.0	21.0
	Throw	7.5	9.0	10.0	11.5	12.5	13.5
	Pressure Loss	.031	.058	.090	.124	.178	.224

Terminal Velocity of 50 FPM

## 472 & 474 Baseboard Return (Page 7, 8)

Face Velocity		300	400	500	600	700
2 feet	CFM	100	130	165	195	230
Ak .325	Ps	.010	.028	.046	.064	.090
4 feet	CFM	195	260	325	390	455
Ak .650	Ps	.015	.026	.040	.060	.078

Velocity measured on the face

## 654, 655 Baseboard/Sidewall Registers (Page 9)

Face Velocity		300	400	500	600	700	800	900	1000
<b>Pressure Loss</b>		<b>.006</b>	<b>.010</b>	<b>.016</b>	<b>.022</b>	<b>.031</b>	<b>.040</b>	<b>.050</b>	<b>.062</b>
8 x 6	CFM	55	72	90	108	125	145	162	180
Ak .180	Throw	7.5	10.0	12.5	15.0	17.5	20.5	23.0	25.0
10 x 6	CFM	70	92	115	140	160	185	205	230
Ak .230	Throw	9.0	11.5	14.5	17.5	20.0	23.0	25.5	29.0
12 x 6	CFM	85	115	145	175	205	230	260	290
Ak .290	Throw	10.0	13.0	17.0	20.0	23.5	26.5	30.0	33.0
14 x 6	CFM	102	135	170	205	240	270	305	340
Ak .340	Throw	11.0	14.5	18.0	22.0	25.5	29.0	32.5	36.0

Terminal Velocity of 75 FPM

## 657/658 Baseboard Return Grille (Page 9)

Average Face Velocity*		300	400	500	600	700
10 x 6	CFM	115	150	190	225	265
Ak .38	Pt	.013	.023	.037	.052	.072
12 x 6	CFM	135	180	230	280	320
Ak .46	Pt	.013	.022	.035	.051	.070
10 x 8	CFM	150	205	255	305	355
Ak .51	Pt	.012	.022	.035	.050	.068
14 x 6	CFM	160	210	265	320	370
Ak .53	Pt	.012	.022	.035	.050	.068
12 x 8	CFM	180	245	305	365	430
Ak .61	Pt	.012	.022	.034	.049	.066
14 x 8	CFM	215	288	360	430	505
Ak .72	Pt	.012	.021	.033	.047	.065
20 x 6	CFM	225	300	375	450	525
Ak .75	Pt	.012	.021	.033	.047	.064
16 x 8	CFM	250	330	415	500	580
Ak .83	Pt	.012	.021	.033	.046	.063
14 x 10 and 24 x 6	CFM	275	365	460	550	640
Ak .92	Pt	.011	.020	.032	.045	.062
14 x 12	CFM	320	430	540	650	755
Ak 1.08	Pt	.011	.020	.031	.045	.060
30 x 6	CFM	335	445	560	670	780
Ak 1.12	Pt	.011	.020	.031	.044	.060
24 x 8	CFM	365	485	605	730	850
Ak 1.21	Pt	.011	.020	.031	.044	.059
20 x 10	CFM	375	500	630	750	880
Ak 1.25	Pt	.011	.019	.030	.043	.059
24 x 10 and 30 x 8	CFM	450	600	750	890	1040
Ak 1.50	Pt	.011	.019	.030	.042	.057
24 x 12	CFM	550	730	910	1100	1270
Ak 1.82	Pt	.010	.018	.029	.041	.056
30 x 10	CFM	575	760	960	1150	1330
Ak 1.91	Pt	.010	.018	.029	.041	.055
30 x 12	CFM	680	900	1130	1350	1570
Ak 2.25	Pt	.010	.018	.028	.040	.054

\*Velocity measured 1" from face

## 664 Baseboard Register (Page 10)

Face Velocity		300	400	500	600	700	800	900	1000
<b>Pressure Loss</b>		<b>.006</b>	<b>.010</b>	<b>.016</b>	<b>.022</b>	<b>.031</b>	<b>.040</b>	<b>.050</b>	<b>.062</b>
8 x 6	CFM	55	70	90	110	125	145	160	180
Ak .180	Throw	5.5	7.0	9.0	10.5	12.5	14.0	16.0	18.0
10 x 6 and 12 x 5	CFM	75	100	125	145	170	195	220	245
Ak .245	Throw	6.0	8.0	10.0	12.0	14.0	16.0	18.0	20.0
14 x 6	CFM	110	145	180	215	252	290	325	360
Ak .360	Throw	7.0	9.5	12.0	14.0	16.5	19.0	21.5	24.0
12 x 8	CFM	130	170	215	255	300	340	385	425
Ak .425	Throw	7.5	10.0	12.5	15.0	18.0	20.5	23.0	25.5

Terminal Velocity of 75 FPM